

FAQ0019

Frequently Asked Questions

AT32F4xx IO speed setting

Questions:

AT32F4xx IO speed setting different from other MCUs

Answer: AT32F4xx IO speed setting are described as follows:

- 1. AT32F4xx IO offers three types of current drive capabilities
 - (1) GPIO DRIVE STRENGTH MODERATE represents moderate sourcing/sinking strength
 - (2) GPIO_DRIVE_STRENGTH_STRONGER represents stronger sourcing/sinking strength
 - (3) GPIO_DRIVE_STRENGTH_MAXIMUM represents maximum sourcing/sinking strength
- 2. If IO speed is set at maximum sourcing strength, and the load is small, it is likely to cause overshoot and vibrating issue on the IO, which may affect applications.
- 3. For general applications

GPIO DRIVE STRENGTH MODERATE is recommended.

For those that require strong current:

GPIO_DRIVE_STRENGTH_STRONGER or GPIO_DRIVE_STRENGTH_MAXIMUM is recommended.

Besides, it is possible to connect a resistor to a reserved IO location in series.

Type: MCU

Applicable products: AT32 MCU family

Main function: GPIO Minor function: None



Document revision history

Date	Revision	Changes
2022.2.16	2.0.0	Initial release



IMPORTANT NOTICE - PLEASE READ CAREFULLY

Purchasers are solely responsible for the selection and use of ARTERY's products and services, and ARTERY assumes no liability whatsoever relating to the choice, selection or use of the ARTERY products and services described herein.

No license, express or implied, to any intellectual property rights is granted under this document. If any part of this document deals with any third party products or services, it shall not be deemed a license grant by ARTERY for the use of such third party products or services, or any intellectual property contained therein, or considered as a warranty regarding the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

Unless otherwise specified in ARTERY's terms and conditions of sale, ARTERY provides no warranties, express or implied, regarding the use and/or sale of ARTERY products, including but not limited to any implied warranties of merchantability, fitness for a particular purpose (and their equivalents under the laws of any jurisdiction), or infringement of any patent, copyright or other intellectual property right.

Purchasers hereby agrees that ARTERY's products are not designed or authorized for use in: (A) any application with special requirements of safety such as life support and active implantable device, or system with functional safety requirements; (B) any air craft application; (C) any automotive application or environment; (D) any space application or environment, and/or (E) any weapon application. Purchasers' unauthorized use of them in the aforementioned applications, even if with a written notice, is solely at purchasers' risk, and is solely responsible for meeting all legal and regulatory requirement in such use.

Resale of ARTERY products with provisions different from the statements and/or technical features stated in this document shall immediately void any warranty grant by ARTERY for ARTERY products or services described herein and shall not create or expand in any manner whatsoever, any liability of ARTERY.

© 2022 Artery Technology-All rights reserved